



Designed for Copier, Laser & Ink-Jet Printers:

Stock White Paper with fantastic print qualities

Uncoated paper with a smooth finish, giving excellent print results using ink-jet & hot fusion toner systems (Mono & Colour). The material is designed for use on most laser printers & copiers especially mid to high-speed machines.

Face material properties

Grammage	65 gsm + or – 4%
Caliper (thickness)	71 microns + or – 5%
Tensile strength N/m	64 MD – 33 CD
Roughness PPS 10	5.0
Opacity	88%
Stiffness.	91 mN CD

Adhesive

A permanent, acrylic based adhesive with good tack & adhesion on a wide range of surfaces. Whilst maintaining good stability during laser printing.

Suitable for use on Dry, Non-Fatty food stuff according to ISEGA food stuffs certification.

Minimum application temp.	+5°C
Storage range once applied	-20°C to +80°C

Backing

A one side clay coated, ECF bleached kraft paper with good lay-flatness & stability

Calliper (thickness)	56 microns + or – 4 microns
Grammage	55 gsm + or – 3 gsm

Environmental & Handling

Paper components are either ECF or TCF grade manufactured using pulp from sustainable, managed resources. All dimensions are nominal target specifications but may vary. All products within our range are manufactured to BRC A standards. The factory is also FSC and ISO14001 certified. Furthermore we are a Zero to landfill certified company. Print room conditions should be at approx. 20°C and between 40% and 60% RH.

Markets and Uses

This is an ideal product for just about every occasion. For small or large office and commercial label requirements. Simple branding labels one or two colours or a simple logo – although the matt face paper will not lift the colours if you need a higher spec finish then please check out our Semi-Gloss or High Gloss materials. **Product and production, Stock Control, despatch, Office Use, Retail, Warehousing, Home Office, Mailings.**

